



Functional Paints

Chalkboard

DESCRIPTION

CHALKBOARD is a modified acrylic based silky matt textured interior paint that features decorative blackboard effect to the surface its applied on.

APPLICATION AREA

Chalkboard is used for decorative purposes on interior walls of buildings, wood, mdf etc.

FEATURES

- It provides perfect background for chalk writing to the surface its applied on,
- It feaures high pigmentation,
- Adheres to the surface perfectly, does not blister neither cracks,
- After reaching its final hardness and durability, it can be easily cleaned with a damp (wet) cloth,
- It can turn all kinds of surface to the writing board (chalkboard) and after it dries it can be written on it with colorful chalks,
- Highly vapour permeable, it enables the vapour to be thrown out and allows the surface to breathe,
- Water-based, it is odour-free; it is harmless to human health and environment.
- Chalkboard offers black, pinky, canary, blue cream and king green.

SURFACE PREPARATION

- Remove all kinds of dirt, oil, blistered paints and dust from the application surfaces, correct the surface defects using SAN DECO ACRYLIC PUTTY INTERIOR
- Surfaces with old paint or surfaces to be painted must be undercoated with SAN DECO UNIPRIMER

APPLICATION INSTRUCTIONS

- Prior to application, dilute CHALKBOARD with 5% of fresh water and mix it homogenously.
- Apply 2 coats with a roller, brush or a spraying method. Wait minimum 3-4 hours before applying second layer.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 2-3 hours for touch dry, 24 hours for complete dry, and after 72 hours the surface is ready to use at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application;

-1 lt covers an area of 12,5 – 20 m²

-1 kg covers an area of 10,0 – 16,8 m²

- The paint consumption for 1 m² area is 50 – 80 ml and 60 - 100 gr.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Functional Paints

Chalkboard

STORAGE

The product should be stored in a sealed package, in a cool and dry place and protected from direct sunlight at temperature between +5°C and +35°C.

HAZAR STATEMENT AND DESCRIPTION

H317 Causes allergic skin reactions.

PRECAUTIONARY STATEMENTS AND DESCRIPTION

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P272 Do not take contaminated clothing out of the office.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or itching occurs: Get medical attention / attention.

P363 Wash contaminated clothing before reuse.

EUH 208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1).

May cause allergic reactions.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. IP.002.ENG - Rev01 May 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88