



Decorative Paints and Coatings

Beton Deco

DESCRIPTION

BETON DECO is an acrylic emulsion based and natural lime added decorative coating material which has gross concrete look on walls. It is suitable for interior and also exterior use if it is desired.

APPLICATION AREA

It can be applied to rough plaster, concrete, mineral surfaces like cement plate, gypsum board, drywall, fixed plywood and surfaces with old paint of interiors and exteriors.

SURFACE PREPARATION

- Clean any dirt, oil, swollen paint and dust on the surface and correct any surface impurities using SAN DECO ACRYLIC PUTTY INTERIOR.
- First surfaces should be applied with SAN DECO DECOPRIMER. It is advised to use the same color of primer with the selected product color.

APPLICATION INSTRUCTIONS

- BETON DECO should be mixed until it is homogenous; if it is needed clean water can be add to attain the application viscosity
- After undercoat is completely dry, BETON DECO should be applied properly to the surface by using trowel as first coat.
- After 5-6 hours later at 23°C, second coat application should be done in the same style with steel trowel and then can be smoothened with trowel.
- For different pattern and thickness application with BETON DECO, different effects can be achieved with trowel.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 5-6 hours for touch dry and 24-48 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

-1 lt covers 2,25 – 2,85 m² of surface

-1 kg covers 1,35 – 1,65 m² of surface

-The paint consumption for 1 m² area is 350 – 440 ml and 600 – 750 gr.

STORAGE

It should be stored in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Decorative Paints and Coatings

Beton Deco

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. DP.019.ENG - Rev01 November 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88