



Exterior Products Range

Dentex

DESCRIPTION

DENTEX is an acrylic emulsion based decorative paint with bright finish.

APPLICATION AREA

DENTEX is used on all kinds of structures; plaster, exposed concrete, brick, wood, briquette, eternite and undercoated metal surfaces with its appropriate primer.

FEATURES

- Thanks to DENTEX's special formulation, it provides the rain water sliding down on the surface without wetting it,
- With its elastic future, it serves as a bridge for the cracks forming on the surface, not affected by the cracks that might occur due to building subsidence,
- Not affected from external factors, and weather conditions like rain, snow, humidity, extreme hot or cold and colors do not fade,
- Due to its high vapor permeability, it allows surface to discharge the steam and breathe,
- As it is water-based, it is harmless to human health and environment.

SURFACE PREPARATION

- Clean all kinds of dirt, oil, blistered paint and dust off the application surface and level the surface with SAN DECO ACRYLIC PUTTY EXTERIOR
- Surfaces with old paint or surfaces to be painted new must be undercoated with SAN DECO UNIPRIMER. It is recommended to use undercoating with the same color as the desired siding color.
- DENTEX DECO product is applied textured to the surface after primed with SAN DECO UNIPRIMER. Dentex must applied after Dentex Deco completely dried.

APPLICATION INSTRUCTIONS

- Dilute DENTEX with 5-10% water prior to application and apply on the surface with roller brush as 2 coats,
- Although the DENTEX product is formulated to be applied on the DENTEX DECO product, it can also be applied as a topcoat on the exterior primed paint and different coating materials.
- Allow minimum 4 hours between each coats,
- The temperature of the application environment must be kept between +5°C and +35°C during application and for 24 hours afterwards.

DRYING TIME

Allow 4-6 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

-1 lt covers 10,0 – 11,0 m² of surface,

-1 kg covers 8,0 – 9,0 m² of surface,

-The paint consumption for 1 m² area is 90 - 100 ml and 110 - 125 gr.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Exterior Products Range

Dentex

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

HAZARD STATEMENT

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH 208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. EP.001.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88