



Exterior Products Range

Densil

DESCRIPTION

DENSIL is an acrylic emulsion based, silicone added, long-lasting, high quality, matt decorative exterior paint.

APPLICATION AREA

DENSIL is used on external sides on plaster, exposed concrete, cement sheet and eternit with suitable undercoating.

FEATURES

- Water repellent thanks to its siliconized feature,
- Resistant against weather conditions like rain, snow, extreme hot or cold and abrasion,
- Gives a modern and clean look to surfaces with decorative non-fading colours,
- Due its high vapor permeability, it allows surface to discharge the steam and breathe,
- Easy application, high coverage,
- As it is water-based, it is harmless to human health and environment.

SURFACE PREPARATION

- Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with SAN DECO ACRYLIC PUTTY EXTERIOR,
- Previously painted surfaces or surfaces that will be painted must be undercoated with SAN DECO UNIPRIMER SILICONE. We recommend using the same colour of undercoat as the selected siding color.

APPLICATION INSTRUCTIONS

- Prior to application, dilute DENSIL with 15-20 % fresh water and mix it well,
- Then apply in 2 coats with roller, brush or spraying method. Allow minimum 4 hours between each coats,
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

-1 lt covers 12,0 – 15,0 m² of surface

-1 kg covers 8,0 – 10,0 m² of surface

-The paint consumption for 1 m² area is 65 -80 ml and 100 - 125 gr.

STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; during and at a temperature between +5°C and +35°C.

DEKA BOYA SANAYİ ve TİC. A.Ş.



Exterior Products Range

Densil

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. EP.003.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88