



## Exterior Products Range

# Dogamin Natural

### DESCRIPTION

DOGAMIN NATURAL is an acrylic emulsion based, decorative mineral coating material with containing natural color stones.

### APPLICATION AREA

DOGAMIN NATURAL is used in exterior faces of all kinds of buildings on rough plaster, exposed concrete, cement sheet and insulation systems as final coat material, along with suitable undercoat.

### FEATURES

- Manufactured in two different sizes; 1 mm and 3mm,
- Vapour permeable, enables the vapour to be thrown out and lets the surface breathe,
- Covers up the faults on the surface with the thick layer of film that forms during application,
- Not affected from external factors, and weather conditions like rain, snow, humid, extreme hot or cold , moreover its colours do not fade,
- Resistant to UV and alkaline,
- As it is water-based, it is harmless to human health and environment,

### SURFACE PREPARATION

Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with SAN DECO ACRYLIC PUTTY EXTERIOR and then previously painted surfaces, or surfaces that will be painted must be undercoated with SAN DECO UNIPRIMER

### APPLICATION INSTRUCTIONS

- Prior to application, dilute DOGAMIN NATURAL with 5% fresh water and mix mineral coating well until it achieves a homogenous consistency,
- Spread DOGAMIN NATURAL mineral coating on the entire surface with equal thickness with steel trowel,
- Finish DOGAMIN NATURAL mineral coating with steel trowel 20 minutes after it is spread on the surface under normal weather conditions,
- The temperature of environment must be kept between +5°C to +35°C within 24 hours during and after the application.

### DRYING TIME

Allow 4-6 hours for touch dry and 24-48 hours for complete dry at 23°C environment conditions.

### THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

#### 1 mm:

-1 lt covers 0,75–0,85 m<sup>2</sup> of surface,

-1 kg covers 0,40–0,45 m<sup>2</sup> of surface,

-The paint consumption for 1 m<sup>2</sup> area is 1175-1330 ml and 2220-2500 gr.

#### 3 mm:

-1 lt covers 0,50–0,60 m<sup>2</sup> of surface,

-1 kg covers 0,25–0,35 m<sup>2</sup> of surface,

-The paint consumption for 1 m<sup>2</sup> area is 1660-2000 ml and 3000-3800 gr.

### DEKA BOYA SANAYİ ve TİC. A.Ş.



## Exterior Products Range

# Dogamin Natural

### STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; and at a temperature between +5°C and +35°C.

### HAZARD STATEMENTS

**H317** May cause an allergic skin reaction.

### PRECAUTIONARY STATEMENTS

**P261** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P272** Contaminated work clothing should not be allowed out of the workplace.

**P280** Wear protective gloves/protective clothing/eye protection/face protection.

**P302 + P352** IF ON SKIN: Wash with plenty of soap and water.

**P333 + P313** If skin irritation or rash occurs: Get medical advice/attention.

**P363** Wash contaminated clothing before reuse.

**EUH208** Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)  
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

#### Product Technical Data Sheet No. EP.009.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

**This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standards of ISO 9001, ISO 14001, ISO 45001.**

#### DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88