



## Exterior Products Range

# Teramix

### DESCRIPTION

TERAMIX is an acrylic emulsion based, grainy textured, decorative exterior coating.

### APPLICATION AREA

TERAMIX is used in exterior faces of all kinds of buildings on rough plaster, exposed concrete, cement sheet and insulation systems as final coat material, along with suitable undercoat.

### SURFACE PREPARATION

- Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with SAN DECO ACRYLIC PUTTY EXTERIOR,
- Previously painted surfaces or surfaces that will be painted must be undercoated with SAN DECO UNIPRIMER We recommend using the same colour of undercoat as the selected siding colour.

### APPLICATION INSTRUCTIONS

- Mix TERAMIX until it achieves a homogenous consistency without diluting,
- Apply TERAMIX in a single coat with a trowel. Adjust application thickness according to the largest texture stones found in the product. Texture the surface with plastic spud using circular motions,
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

### DRYING TIME

Allow 4-6 hours for touch dry and 24-48 hours for complete dry at 23°C environment conditions.

### THEORETICAL CONSUMPTION

Depending on surface smoothness, porosity and application methods, for a single coat application;

#### 1mm

-1 lt covers 0,95– 1,75 m<sup>2</sup> of surface,

-1 kg covers 0,55– 1,00 m<sup>2</sup> of surface,

-The paint consumption for 1 m<sup>2</sup> area is 550 -1050 ml and 1000 - 1800 gr.

#### 1,2mm

-1 lt covers 0,85– 1,50 m<sup>2</sup> of surface,

-1 kg covers 0,50– 0,85 m<sup>2</sup> of surface,

-The paint consumption for 1 m<sup>2</sup> area is 700 -1100 ml and 1200 - 2000 gr.

#### 1,5mm

-1 lt covers 0,80– 1,00 m<sup>2</sup> of surface,

-1 kg covers 0,45– 0,60 m<sup>2</sup> of surface,

-The paint consumption for 1 m<sup>2</sup> area is 950 -1250 ml and 1700 - 2200 gr.

#### 2mm

-1 lt covers 0,60 – 0,90 m<sup>2</sup> of surface,

-1 kg covers 0,30 – 0,50 m<sup>2</sup> of surface,

-The paint consumption for 1 m<sup>2</sup> area is 1200 -1800 ml and 2200 - 3200 gr.

### DEKA BOYA SANAYİ ve TİC. A.Ş.



## Exterior Products Range

# Teramix

### 3mm

- 1 lt covers 0,45 – 0,55 m<sup>2</sup> of surface,
- 1 kg covers 0,25 – 0,30 m<sup>2</sup> of surface,
- The paint consumption for 1 m<sup>2</sup> area is 2000 -2500 ml and 3500 - 4500 gr.

### STORAGE

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; during and at a temperature between +5°C and +35°C.

### HAZARD STATEMENTS

**H317** May cause an allergic skin reaction.

### PRECAUTIONARY STATEMENTS

- P261** Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272** Contaminated work clothing should not be allowed out of the workplace.
- P280** Wear protective gloves/protective clothing/eye protection/face protection.
- P302 + P352** IF ON SKIN: Wash with plenty of soap and water.
- P333 + P313** If skin irritation or rash occurs: Get medical advice/attention.
- P363** Wash contaminated clothing before reuse.
- EUH208** Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)  
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

#### Product Technical Data Sheet No. EP.010.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

**This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.**

#### DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88