



## Exterior Products Range

## Travertex

## DESCRIPTION

TRAVERTEX is an acrylic emulsion based, line textured decorative exterior coating.

## APPLICATION AREA

TRAVERTEX is used in exterior faces of all kinds of buildings on rough plaster, exposed concrete, cement sheet and insulation systems as final coat material, along with suitable undercoat.

## FEATURES

- Manufactured 3mm,
- More elastic than cement based products, and serves as a bridge for the cracks on the application surface,
- Not affected by the cracks forming due to building settling,
- Covers up the faults on the surface with the thick layer of film that forms during application, Resistant to UV and alkaline,
- Not affected from external factors, and weather conditions like rain, snow, humid, extreme hot or cold and also its colours do not fade,
- Due its high vapor permeability, it allows surface to discharge the steam and breathe, □ As it is water-based, it is harmless to human health and environment.

## SURFACE PREPARATION

- Clean all dirt, oil, blistered paint and dust off the application surface; level the surface defects with SAN DECO ACRYLIC PUTTY EXTERIOR
- Previously painted surfaces or surfaces that will be painted must be undercoated with SAN DECO UNIPRIMER We recommend using the same colour of undercoat as the selected siding color.

## APPLICATION INSTRUCTIONS

- Mix TRAVERTEX until it achieves a homogenous consistency without diluting,
- Apply TRAVERTEX in a single coat with a trowel,
- Adjust application thickness according to the largest texture stones found in the product. Texture the surface with plastic spud using circular motions,
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

## DRYING TIME

Allow 4-6 hours for touch dry and 24-48 hours for complete dry at 23°C environment conditions.



## Exterior Products Range

**Travertex****THEORETICAL CONSUMPTION**

Depending on surface smoothness, porosity and application methods, for a single coat application;  
3 mm:

- 1 lt covers 0,5– 0,6 m<sup>2</sup> of surface,
- 1 kg covers 0,3 – 0,4 m<sup>2</sup> of surface,
- The paint consumption for 1 m<sup>2</sup> area is 1685 -1965 ml and 2500 - 3500 gr.

**STORAGE**

It should be stored in a sealed package, in a cool and dry place and protected from direct sunlight; and at a temperature between +5°C and +35°C.

**HAZARD STATEMENTS**

H317 May cause an allergic skin reaction.

**PRECAUTIONARY STATEMENTS**

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P363 Wash contaminated clothing before reuse.
- EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1) May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

Product Technical Data Sheet No. EP.011.ENG - Rev01 February 2022

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the healthsafety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Mermerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88