



Interior Products Range

Proplas

DESCRIPTION

It is an acrylic-based emulsion, matt, decorative interior paint.

APPLICATION AREA

PROPLAS is applied on properly prepared interior mineral surfaces like rough (black) plaster, concrete, cement sheet, plaster panel and previously painted surfaces with a suitable undercoat.

SURFACE PREPARATION

- Clean all dirt, oil, blistered paint and dust from the application surface; level the surface defects with SAN DECO ACRYLIC PUTTY INTERIOR.
- Undercoat the previously painted or to be painted surfaces with SAN DECO UNIPRIMER.

APPLICATION INSTRUCTIONS

- Prior to application, mix PROPLAS homogenously by diluting it with (maximum) %20 of fresh water.
- Apply in 2 coats with a roller, brush or spraying method. Wait a minimum of 4 hours between coats.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

DRYING TIME

Allow 4-5 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

1 liter of paint covers an area of 14,0 – 16,5 m²

1 kg of paint covers an area of 8 – 9,5 m²

The paint consumption for 1 m² area is 60-70 ml and 105-120 gr.

STORAGE

It should be stored in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

PRECAUTIONARY STATEMENTS

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

EUH208 Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)

May produce an allergic reaction.


DEKA BOYA SANAYİ ve TİC. A.Ş.



Interior Products Range

Proplas

Note: For more information, please check the Safety Data Sheet (SDS) of the product



Product Technical Data Sheet No. IP.004.ENG - Rev00 March 2020

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.

DEKA BOYA SANAYİ ve TİC. A.Ş.

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88