



Interior Products Range

# Super Tavan (Super Ceiling)

## DESCRIPTION

SUPER CEILING is an acrylic- based emulsion extra white matt ceiling paint.

## APPLICATION AREA

SUPER CEILING is applied on mineral new ceilings like rough plaster, concrete, cement sheet and old painted ceilings, after preparation of the surface.

## SURFACE PREPARATION

- After removing all kind of dirt, oil, blistered paint and dust from the application surfaces, the defects of the surface should be corrected with SAN DECO ACRYLIC PUTTY INTERIOR.
- Previously painted surfaces and surfaces which will be painted should be undercoated by SAN DECO UNIPRIMER.

## APPLICATION INSTRUCTIONS

- Prior to application, mix well SUPER CEILING by diluting it with (maximum) 20-25% of fresh water.
- Apply two coats with a brush, roller or a spraying system and wait minimum 2 hours before applying the second coat.
- The environment of application must be kept between +5°C to +35°C within 24 hours during and after the application.

## DRYING TIME

Allow 2-4 hours for touch dry and 24 hours for complete dry at 23°C environment conditions.

## THEORETICAL CONSUMPTION

Depending on the surface smoothness, its porosity and the application methods, for a single coat application:

1 liter of paint covers an area of 14,5 – 15,5 m<sup>2</sup>

1 kg of paint covers an area of 8,5 – 9,5 m<sup>2</sup>

The paint consumption for 1 m<sup>2</sup> area is 65 - 70 ml and 105 - 120 gr.

## STORAGE

It should be stored in a sealed package, cool and dry place and protected from direct sunlight; at a temperature between +5°C and +35°C.

## HAZARD STATEMENTS

**H317** May cause an allergic skin reaction.

## PRECAUTIONARY STATEMENTS

**P261** Avoid breathing dust/fume/gas/mist/vapours/spray.

**P272** Contaminated work clothing should not be allowed out of the workplace.

**P280** Wear protective gloves/protective clothing/eye protection/face protection.

**P302 + P352** IF ON SKIN: Wash with plenty of soap and water.

**P333 + P313** If skin irritation or rash occurs: Get medical advice/attention.

**P363** Wash contaminated clothing before reuse.

**DEKA BOYA SANAYİ ve TİC. A.Ş.**



Interior Products Range

# Super Tavan (Super Ceiling)

**EUH208** Contains chloromethylisothiazolinone and methylisothiazolinone (3:1)  
May produce an allergic reaction.

Note: For more information, please check the Safety Data Sheet (SDS) of the product

**Product Technical Data Sheet No. IP.005.ENG - Rev00 March 2020**

Since this technical sheet is prepared on the basis of laboratory data under normal conditions, consult the technical staff for details that are not sufficient above. Otherwise, errors that will occur as a result of insufficient information do not impose responsibility on the manufacturer. Deka Boya San. ve Tic. A.S. reserves the right to change this information. If necessary, you can find detailed information about the health-safety-transportation risks and precautions of the products from the Material Safety Data Sheet.

**This product is produced by Deka Boya Sanayi ve Tic. A.S. who is also certified by the standarts of ISO 9001, ISO 14001, ISO 45001.**

**DEKA BOYA SANAYİ ve TİC. A.Ş.**

Merkez: Yukarı Dudullu Mah. Necip Fazıl Bulvarı Keyap Çarşısı D2 Blok No:61 Ümraniye/İstanbul Tel: +90 (216) 575 56 56  
Fabrika: S.S. İstanbul Memerciler Küçük Sanayi Sitesi 34.Cd. No:3 Dilovası/Kocaeli Tel: +90 (262) 728 10 88