

GALAXY/GALAXY FOSFOR

Pearlescent Flake Textured Decorative Paint

GALAXY is a decorative paint with pearlescent flake particles, developed for interior use.

GALAXY PHOSPHOR differs from the standard GALAXY product as it contains phosphorescent flake particles.














Due to its phosphor pigment content, Galaxy Phosphor stores the energy it absorbs from daylight or artificial light sources and emits it in dark environments.

It provides an antique appearance on the applied surface.

Thanks to its transparent film structure, it does not alter the base color of the surface.

It is water-based, environmentally friendly, and harmless to human health.

 CONTENT: <i>Acrylic-based, water-based, flecked</i>	 PACKAGING: <i>Galaxy: 2,5 KG - Galaxy Fosfor: 1L ; 2,5L</i>
 THINNING: <i>Ready to use, do not thin.</i>	 DRYING TIME: <i>Drying Time Touch dry (at 23°C): 4-5 hours *drying time may be longer at higher relative humidity and lower temperature.</i>
 PRIMER: <i>San Deco Decoprimer</i>	 Fully Dry: <i>24-48 hours</i>
 APPLICATION TOOL: <i>Brush, spatula</i>	 COLORING: <i>Galaxy Color Chart</i>
 NUMBER of COATS: <i>1</i>	 VOC: <i>Limit value EU (Directive 2004/42/EC) Category A/I: Decorative effect coatings (water-based): 200 g/l (2010) GALAXY: contains maximum 15 g/l VOC GALAXY PHOSPHOR: contains maximum 22 g/l VOC</i>
 STORAGE and SHELF LIFE: <i>Can be stored for 1 year in its unopened package, in a cool and dry place, protected from direct sunlight, between +5°C and +35°C.</i>	

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*



Galaxy:
1 L covers 3,75-4,6 m²,
1 kg covers 3,65-4,5 m².
For 1 m² of surface, paint consumption is
215-265 ml and 220-270 g.

Galaxy Phosphor:
1 L covers 3,1-3,5 m²,
1 kg covers 2,95-3,35 m².
For 1 m² of surface, paint consumption is 285-320 ml
and 300-340 g.

APPLICATION AREA

It is used on interior surfaces such as walls, plaster, fair-faced concrete, and wood, following appropriate surface preparation and the application of its own primer.

SURFACE PREPARATION

All kinds of dirt, oil, loose or blistered paint, and dust should be thoroughly removed from the application surface. Surface imperfections should be repaired with San Deco Acrylic Putty Fine, and then the surface should be primed with San Deco Decoprimer.

SURFACE CONDITIONS

During application and until the product is fully dry, ensure that the ambient and surface temperature is not below +5°C and not above +35°C.

Ambient humidity should be below 75%, and surface moisture should be below 10%.

APPLICATION

Before starting the application, Galaxy/Galaxy Phosphor should be mixed thoroughly without dilution until a homogeneous consistency is achieved.

The first coat is applied to the surface with a brush. After waiting approximately 25 minutes, the desired appearance is obtained by flattening the surface with a plastic spatula.

Different decorative textures can be achieved depending on the application technique.

For more detailed information on application, product application videos can be viewed.

If more than one batch number is used within the same project, it is recommended to mix batches equally before application to prevent possible shade differences.

Local retouching is not recommended. In cases requiring retouching, it is advised to reapply the product to the entire affected surface.

HAZARD & PRECAUTIONARY STATEMENTS

H317: May cause an allergic skin reaction.

EUH071: Corrosive to the respiratory tract.

P261: Avoid breathing dust/fume/gas/mist/vapors/spray.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash before reuse.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Note: For more detailed information, please refer to the product's Safety Data Sheet (SDS).

This technical data sheet has been prepared based on laboratory data under standard conditions. For further details not covered here, please consult technical personnel. Otherwise, any errors arising from insufficient information are not the manufacturer's responsibility. The right to revise this information is reserved by our company. For detailed information regarding the product's health, safety, transport risks, and precautions, please refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., which holds certifications in compliance with ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001 standards.