SAN DECO®
Paint Manufacturing & Distribution

NOSTALGIE FINISH

Decorative Transparent Topcoat Paint

NOSTALGIE FINISH is a transparent, decorative topcoat paint for interior surfaces.

REACH compliant | TINTABLE | WATER BASED | LOW VOC

Provides a matte, shaded antique appearance on the surface.

Water-based; environmentally friendly and safe for human health.

CONTENT: *Acrylic-based, water-based.*

THINNING: *Ready to use; do not dilute.*

PRIMER: *San Deco Decoprimer.*

APPLICATION TOOL: *Sponge, roller.*

NUMBER of COATS: *1*

STORAGE and SHELF LIFE:
Unopened packaging can be stored for 2 years between +5°C and +35°C in a cool and dry place, protected from direct sunlight.

PACKAGING: *0.75 L*

DRYING TIME: *Drying Time Touch dry (at 23˚C): 4-5 hours*
**drying time may be longer at higher relative humidity and lower temperature.*

Fully Dry: *24 hours*

COLORING: *Liberte Art, Vision systems - 70 Colors*

VOC:
EU Limit Value (Directive 2004/42/EC)
Category A/l: Decorative effect coatings (water-based): 200 g/L (2010)
NOSTALGIE FINISH: Maximum content: 53.5 g/L VOC

CONSUMPTION - Single Coat : *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*

1 L covers 10,6-14,7 m^2
1 kg covers 9-12,5 m^2
For 1 m^2: approx. 70-90 ml and 80-110 g.

APPLICATION AREA

After proper substrate preparation, it is applied over Nostalgie Base or other decorative coating products on interior walls, plaster, exposed concrete, and wooden surfaces.

SURFACE PREPARATION

All dirt, oil, loose paint, and dust must be removed from the application surface. Surface imperfections must be repaired with San Deco Acrylic Putty Fine and then primed with San Deco Decoprimer.

Applied over Nostalgie Base or other decorative coating products.

SURFACE CONDITIONS

During application and until complete curing, substrate and ambient temperature must be between +5°C and +35°C.

Ambient humidity should be below 75% during application.

Substrate moisture content should be below 10%.

APPLICATION

Two (2) days after Nostalgie Base application, Nostalgie Finish is applied using circular motions with a roller.

Depending on the desired look, it may be applied in thin or thick layers, or color tones may be adjusted by wiping with a sponge.

For more detailed application information, product application videos may be viewed.

When using multiple batch numbers in the same project, mix batches proportionally prior to application to avoid batch differences.

Local retouching is not recommended. If retouching is required, reapplication over the entire damaged surface is advised.

HAZARD & PRECAUTIONARY STATEMENTS

H317: May cause allergic skin reactions.
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.
P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364: Take off contaminated clothing and wash it before reuse.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P321: Specific treatment required (see product label).
P272: Contaminated work clothing should not be allowed outside the workplace.

Note: Refer to the Safety Data Sheet (SDS) for additional information.

This technical data sheet is prepared based on laboratory results obtained under standard conditions. For details not covered here, consult technical personnel. Otherwise, the manufacturer cannot be held responsible for errors resulting from insufficient information. The right to revise this document is reserved. For detailed information regarding health, safety, and transportation risks, consult the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001.