

# TRAVERTINO

## Travertine and Natural Stone Effect Decorative Coating












TRAVERTINO is a mineral-based decorative coating that creates a travertine appearance on the applied surface.




*Allows creating various textures using different application techniques.*

*High water vapor permeability allows moisture to escape, enabling the surface to breathe.*

*Water-based; environmentally friendly and safe for human health.*

|   |   |
|---|---|
|  <b>CONTENT:</b> <i>Acrylic-based - water-based</i>  |  <b>PACKAGING:</b> <i>10 KG; 20 KG.</i>  |
|  <b>THINNING:</b> <i>Ready to use; do not dilute.</i>  |  <b>DRYING TIME:</b> <i>Drying Time Touch dry (at 23 °C): 2-3 hours<br/>*drying time may be longer at higher relative humidity and lower temperature.</i>                            |
|  <b>PRIMER:</b> <i>San Deco Decoprimer</i>   |  <b>Fully Dry:</b> <i>48 hours</i>   |
|  <b>APPLICATION TOOL:</b> <i>Steel trowel -Texture tool</i>  |  <b>COLORING:</b> <i>-</i>   |
|  <b>NUMBER of COATS:</b> <i>2</i>  |  <b>VOC:</b><br><i>EU Limit Value (Directive 2004/42/EC)<br/>Category A/I: Decorative effect coatings (water-based): 200 g/L (2010)<br/>TRAVETINO: Maximum content: 46.2 g/L VOC</i> |
|  <b>STORAGE and SHELF LIFE:</b><br><i>Can be stored unopened for 2 years<br/>between +5°C and +35°C in a cool, dry<br/>place protected from direct sunlight.</i> |   |

**CONSUMPTION - Two Coats :** *Consumption may vary depending on the type, absorbency, and structure of the surface, as well as application techniques. For precise consumption, a controlled sample application should be performed.*

 1 L covers 0,7-0,95 m<sup>2</sup>  
1 kg covers 0,4-0,65 m<sup>2</sup>  
For 1 m<sup>2</sup>: approx. 1000-1400 ml and 1800-2500 g.

### APPLICATION AREA

After appropriate substrate preparation, it should be applied with its own primer on interior walls, plaster, exposed concrete, and wooden surfaces.

### SURFACE PREPARATION

All dirt, oil, loose paint, and dust must be removed from the application surface.

Surface defects should be repaired with San Deco Acrylic Putty Fine and then primed with San Deco Decoprimer.

### SURFACE CONDITIONS

During application and until full curing is complete, surface and ambient temperature must be between +5°C and +35°C.

Ambient humidity should be below 75% during application.

Surface moisture content should be below 10%.

### APPLICATION

Travertino is applied without dilution using a steel trowel, with the first coat being at least 1 mm thick.

After a minimum of 6 hours, the second coat is applied.

Before the second coat dries completely, texture is created using a texture tool.

To achieve a smooth final appearance, the surface is polished with a steel trowel.

For detailed application information, product application videos may be viewed.

If multiple batch numbers are used in the same project, mix the batches proportionally before application to avoid color or texture differences.

Local touch-ups are not recommended. If retouching is required, the entire damaged area should be reapplied.

### HAZARD & PRECAUTIONARY STATEMENTS

- H317: May cause allergic skin reactions.  
P261: Avoid breathing dust/fume/gas/mist/vapors/spray.  
P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.  
P362 + P364: Remove contaminated clothing and wash before reuse.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P321: Specific treatment required (see product label).  
P272: Contaminated work clothing must not be taken outside the workplace.

Note: Refer to the Safety Data Sheet (SDS) for more information.

This technical data sheet is prepared based on laboratory results under standard conditions. For additional details not included here, consult technical personnel. The manufacturer cannot be held responsible for errors resulting from insufficient information. The right to revise this document is reserved. For detailed health-safety-transportation information, refer to the Material Safety Data Sheet (MSDS).

This product is manufactured by Deka Boya Sanayi ve Tic. A.Ş., certified to ISO 9001, ISO 14001, ISO 14064, ISO 45001, and ISO 27001.